

# FLOTATION 648

<b>TIRE SIZE</b>	<b>850/50 - 30.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALPRESS / SKÖRDEMASKIN / SPRIDARE / SKÖRDEMASKIN / ARBETSFORDON
<b>VERSION</b>	HD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	176 A8/173 B
<b>LI/SS FREE ROLLING</b>	189 A8/185 B



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94030286	<b>RC (IN)</b>	194.3
<b>SW (IN)</b>	33.5	<b>RIM REC</b>	AG 28.00
<b>OD (IN)</b>	65.0	<b>ECE</b>	E11-106R-004566
<b>SLR (IN)</b>	28.0	<b>PR</b>	18

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33	34	36
<b>5 FR</b>	30280	31030	31790
<b>10 FR</b>	27250	27930	28610
<b>20 FR</b>	24220	24820	25430
<b>25 FR</b>	21630	22170	22710
<b>30 FR</b>	19470	19950	20390
<b>5 DW</b>	20870	21380	21910
<b>10 DW</b>	18780	19250	19720
<b>20 DW</b>	16690	17110	17530
<b>25 DW</b>	14900	15280	15650
<b>30 DW</b>	13410	13750	14330

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.