

AGRIMAX RT 765

TIRE SIZE	480/70 R 24
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
VERSION	SPECIAL
TIRE TYPE	TL
LI/SS	138 D



РАЗМЕРЫ US STANDARD

USA CODE	94062270	RC (IN)	153.3
SW (IN)	18.9	RIM REC	W 15 L
OD (IN)	51.8	RIM ALT	W 14 L; W 16 L
SLR (IN)	22.8	ECE	E11-106R-005519

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
40	2870	3340	3800	4280	4740	5200
30	3010	3510	4000	4490	4980	5470
25	3140	2650	4170	4670	5190	5700
20	3300	3840	4380	4920	5460	5990
5 LT	3850	4480	5100	5730	6360	6980
5 HT	3300	3840	4380	4920	5460	5990

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.