


# TR 390

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>28L - 26</b>  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  BIAS |
| <b>MACHINERY</b>    | TRAILER / IMPLEMENTS /<br>COMPACTOR  |
| <b>VERSION</b>      | DUAL BEAD HD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 168 A8   |



## DIMENSIONS US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94047048 | <b>RC (IN)</b> | 178.9           |
| <b>SW (IN)</b>  | 28.1     | <b>RIM REC</b> | DW 25 B         |
| <b>OD (IN)</b>  | 61.4     | <b>RIM ALT</b> | DW 23 B         |
| <b>SLR (IN)</b> | 27.2     | <b>ECE</b>     | E11-106R-004609 |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>42</b> |
| 25               | 12350     |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.