


FL 630 ULTRA

TIRE SIZE	560/60 R 22.5
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	ESPARCIDOR / CAMIÓN CISTERNA / REMOLQUE / MAQUINARIA AGRÍCOLA
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	161 D ; 172 A8



DIMENSIONES US STANDARD

CÓDIGO USA	94052509	RC (IN)	148.0
SW (IN)	21.4	RIM REC	AG 16.00
OD (IN)	49.0	RIM ALT	16.00 ; 17.00 ; AG 20.00
SLR (IN)	21.1	ECE	E11-106R-003013

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58
45	2980	3390	3810	4740	5390	6230	7050	7700	8450	9280
40	3260	3730	4190	5200	5920	6830	7750	8470	9280	10200
30	3960	4520	5070	6300	7160	8280	9390	10250	11240	12350
25	4450	5080	5700	7090	8060	9310	10560	11530	12640	13890
20	4940	5630	6320	7860	8940	10320	11710	12790	14020	15400
15	5160	5890	6610	8020	9350	10800	12260	13380	14670	16110
5	5870	6700	7530	9370	10650	12300	13950	15230	16710	18350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.