

AGRIMAXFACTOR

TIRE SIZE	600/70 R 28
UM	US STANDARD
MACHINERY	ТРАКТОР-ТЯГАЧ
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	157 D ; 160 A8



РАЗМЕРЫ US STANDARD

USA CODE	94071135	RIM REC	DW 20 B
SW (IN)	24.1	RIM ALT	DW 18 L ; W 18 L
OD (IN)	61.1	ECE	E11-106R-007655
SLR (IN)	28.1	TRA CODE	R1W
RC (IN)	183.7	TREAD DEPTH (32 nd)	71.82

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
40	4280	4920	5640	6370	7100	7830	8550	9090
30	4500	5170	5930	6690	7460	8220	8980	9560
25	4680	5390	6180	6980	7780	8580	9370	9960
15	4930	5650	6490	7330	8170	9010	9840	10460
5 LT	5730	6590	7560	8540	9510	10490	11460	12190
5 HT	4930	5650	6490	7330	8170	9010	9840	10460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.