

# FLOTATION 648

|                           |   |
|---------------------------|---|
| <b>TIRE SIZE</b>          | <b>650/65 - 30.5</b>  |
| <b>UM</b>                 | US STANDARD   |
| <b>CONSTRUCTION</b>       | ⊗ BIAS  |
| <b>MACHINERY</b>          | ENFARDADEIRA DE FENO / CEIFEIRA /<br>ESPALHADOR / CEIFEIRA /<br>IMPLEMENTOS AGRÍCOLAS |
| <b>VERSÃO</b>             | STANDARD  |
| <b>TIRE TYPE</b>          | TL  |
| <b>LI/SS DRIVE WHEEL</b>  | 162 A8/158 B  |
| <b>LI/SS FREE ROLLING</b> | 174 A8/170 B  |



## DIMENSÕES US STANDARD

|                   |          |                |                 |
|-------------------|----------|----------------|-----------------|
| <b>CÓDIGO USA</b> | 94006458 | <b>RC (IN)</b> | 194.3           |
| <b>SW (IN)</b>    | 26.4     | <b>RIM REC</b> | AG 20.00        |
| <b>OD (IN)</b>    | 65.4     | <b>ECE</b>     | E11-106R-004558 |
| <b>SLR (IN)</b>   | 28.0     | <b>PR</b>      | 12              |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI    | 22    | 23    | 25    |
|--------------|-------|-------|-------|
| <b>5 FR</b>  | 19210 | 19950 | 20680 |
| <b>10 FR</b> | 17290 | 17960 | 18610 |
| <b>20 FR</b> | 15370 | 15960 | 16540 |
| <b>25 FR</b> | 13720 | 14250 | 14770 |
| <b>30 FR</b> | 12360 | 12830 | 13230 |
| <b>5 DW</b>  | 13620 | 14150 | 14660 |
| <b>10 DW</b> | 12270 | 12730 | 13190 |
| <b>20 DW</b> | 10900 | 11320 | 11730 |
| <b>25 DW</b> | 9730  | 10110 | 10470 |
| <b>30 DW</b> | 8760  | 9090  | 9370  |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.