


# AGRIMAXFACTOR

<b>TYRE SIZE</b>	<b>360/70 R 24</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	122 D ; 125 A8



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	357	<b>RIM REC</b>	W 11
<b>OD (MM)</b>	1140	<b>RIM ALT</b>	W 10; W 12
<b>SLR (MM)</b>	522	<b>ECE</b>	E11-106R-0010946
<b>RC (MM)</b>	3386	<b>SRI</b>	550

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6
65	825	960	1095	1230	1365	1500
50	870	1010	1150	1295	1435	1575
40	905	1055	1205	1350	1500	1650
30	950	1105	1260	1415	1570	1725
10 LT	1110	1290	1470	1650	1830	2010
10HT	950	1105	1260	1415	1570	1725

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.