

TR 882

TIRE SIZE	400/60 - 15.5
UM	IS STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ПРИЦЕП
VERSION	HD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	132 A8
LI/SS FREE ROLLING	145 A8



РАЗМЕРЫ IS STANDARD

SW (MM)	400	RIM REC	AG 13.00
OD (MM)	875	ECE	E4-106R-001879
SLR (MM)	378	PR	14
RC (MM)	2605	SRI	410

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.60
10 FR	4060
25 FR	3450
30 FR	3250
40 FR	2900
10 DW	2800
25 DW	2380
30 DW	2240
40 DW	2000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.