


# AGRIMAX RT 955

|                     |  |
|---------------------|--|
| <b>TYRE SIZE</b>    | <b>230/95 R 32</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | IMPLEMENTS   |
| <b>VERSION</b>      | STANDARD   |
| <b>TL/TT</b>        | TL   |
| <b>LI/SS</b>        | 128 A8/B   |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94026678 | <b>RC (IN)</b> | 150.0          |
| <b>SW (IN)</b>  | 9.0      | <b>RIM REC</b> | W 7            |
| <b>OD (IN)</b>  | 49.3     | <b>RIM ALT</b> | W 8            |
| <b>SLR (IN)</b> | 23.0     | <b>ECE</b>     | E4-106R-000764 |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI | 12   | 17   | 23   | 29   | 35   | 41   | 46   | 52   | 58   | 64   |
|-----------|------|------|------|------|------|------|------|------|------|------|
| 30        | 1550 | 2030 | 2470 | 2700 | 2870 | 3140 | 3420 | 3690 | 3960 | -    |
| 25        | 1550 | 2030 | 2470 | 2700 | 2870 | 3140 | 3420 | 3690 | 3960 | -    |
| 20        | 1660 | 2170 | 2650 | 2900 | 3060 | 3360 | 3660 | 3960 | 4250 | -    |
| 5         | 1850 | 2330 | 2870 | 3390 | 3940 | 4060 | 4530 | 5000 | 5480 | 5950 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.