

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 600/70 R 28 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | PULVERIZADOR AGRÍCOLA / TRATOR / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS |
| VERSÃO | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 157 D |



DIMENSÕES IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 591 | RIM REC | DW 18 L |
| OD (MM) | 1551 | RIM ALT | DW 20 B |
| SLR (MM) | 696 | ECE | E11-106R-006861 |
| RC (MM) | 4692 | SRI | 725 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 | 2.0 | 2.4 |
|------------|------|------|------|------|------|------|------|------|
| 65 | 1940 | 2230 | 2560 | 2890 | 3220 | 3550 | 3880 | 4125 |
| 50 | 2040 | 2345 | 2690 | 3035 | 3385 | 3730 | 4075 | 4335 |
| 40 | 2125 | 2445 | 2805 | 3165 | 3530 | 3890 | 4250 | 4520 |
| 30 | 2235 | 2565 | 2945 | 3325 | 3705 | 4085 | 4465 | 4745 |
| 10 LT | 2600 | 2990 | 3430 | 3875 | 4315 | 4760 | 5200 | 5530 |
| 10HT | 2235 | 2565 | 2945 | 3325 | 3705 | 4085 | 4465 | 4745 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.