

# AGRIMAX RT 855

|                     |   |
|---------------------|---|
| <b>TIRE SIZE</b>    | <b>340/85 R 24</b>  |
| <b>UM</b>           | IS STANDARD   |
| <b>CONSTRUCTION</b> |   |
| <b>MACHINERY</b>    | SPRAYER / VINEYARD HARVESTER /<br>TRACTOR / HARVESTER /<br>IMPLEMENTS |
| <b>VERSION</b>      | STANDARD  |
| <b>TL/TT</b>        | TL  |
| <b>LI/SS</b>        | 125 A8/B  |



## DIMENSIONS IS STANDARD

|                 |      |                |                |
|-----------------|------|----------------|----------------|
| <b>SW (MM)</b>  | 353  | <b>RIM REC</b> | W 12           |
| <b>OD (MM)</b>  | 1188 | <b>RIM ALT</b> | W 11           |
| <b>SLR (MM)</b> | 532  | <b>ECE</b>     | E4-106R-000604 |
| <b>RC (MM)</b>  | 3542 | <b>SRI</b>     | 575            |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6  | 0.8  | 1.0  | 1.2  | 1.4  | 1.6  |
|------------|------|------|------|------|------|------|
| 50         | 910  | 1060 | 1205 | 1355 | 1505 | 1650 |
| 40         | 910  | 1060 | 1205 | 1355 | 1505 | 1650 |
| 30         | 975  | 1135 | 1295 | 1455 | 1615 | 1770 |
| 10 LT      | 1220 | 1420 | 1620 | 1820 | 2020 | 2215 |
| 10 HT      | 975  | 1135 | 1295 | 1455 | 1615 | 1770 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.