


MULTIMAX MP 522



TIRE SIZE	400/70 R 24 IND
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CARGADORA COMPACTA / ELEVADOR TELESCÓPICO / CARGADORA COMPACTA / ELEVADOR TELESCÓPICO
VERSIÓN	STANDARD
TIRE TYPE	TL
LI/SS	152 A8/B

DIMENSIONES US STANDARD

CÓDIGO USA	94051403	RC (IN)	138.9
SW (IN)	15.9	RIM REC	13
OD (IN)	46.1	RIM ALT	DW 12; 13 SDC; DW 13; DW 13 L; DW 14 L
SLR (IN)	21.0	ECE	E11-106R-002964

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	23	29	35	41	46	51	58	61	64
30	3760	4460	5090	5800	6500	6970	7830	-	-
25	3760	4460	5090	5800	6500	6970	7830	-	-
20	4020	4780	5450	6210	6960	7460	8380	-	-
15	4180	4960	5650	6440	7220	7750	8700	-	-
5 CYC.	4590	5640	6640	7640	8700	9460	10690	11280	11740
STATIC	7020	8640	10170	11710	13330	14490	16390	17280	18000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.