

# MAGLIFT



**MAGLIFT**  
S O L I D T I R E S

# MAGLIFT



MAGLIFT has been particularly designed for forklift in industrial and logistic operations. This solid tire features high load capacity and outstanding comfort. MAGLIFT shows excellent cut and chip resistance resulting in a long tire life. Its reinforced structure eliminates slippage risks whilst the special bead shape simplifies mounting operations on the rim.



| SIZE | TT/TL                  | STAR RATING | LI/SS | RIM                                                                                |                                                                                     | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION  |
|------|------------------------|-------------|-------|------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|--------------|------------|-------------|------------|----------|
|      |                        |             |       | REC RIM                                                                            | ALT RIM                                                                             |              |            |             |            |          |
|      |                        |             |       |  |  |              |            |             |            |          |
| Ø8"  | 18X7 -8 (180/70 - 8)   | -           | -     |                                                                                    |                                                                                     |              | 457        | 0           | 0          | STD      |
|      | 15X4.5 -8 (125/75 - 8) | -           | -     |                                                                                    |                                                                                     |              | 378        | 0           | 0          | LIP - NM |
|      | 15X4.5 -8 (125/75 - 8) | -           | -     | -                                                                                  | -                                                                                   |              | 378        | 0           | 0          | STD      |
|      | 16X6 -8 (150/75 - 8)   | -           | -     |                                                                                    | -                                                                                   |              | 421        | 0           | 0          | LIP      |
|      | 5.00 - 8               | -           | -     | -                                                                                  | -                                                                                   |              | 462        | 0           | 0          | STD      |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

| SIZE                    | TT/TL | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION  |
|-------------------------|-------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|----------|
|                         |       |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |          |
|                         |       |             |       |  |  |              |            |             |            |          |
| 5.00 - 8                | -     | -           | -     | 3.00 D - 8                                                                        | -                                                                                  |              | 462        | 0           | 0          | LIP      |
| 5.00 - 8                | -     | -           | -     | 3.00 D - 8                                                                        | -                                                                                  |              | 462        | 0           | 0          | LIP - NM |
| 15X4.5 - 8 (125/75 - 8) | -     | -           |       | 3.00 D - 8                                                                        | -                                                                                  |              | 378        | 0           | 0          | LIP      |
| 4.00 - 8                | -     | -           | -     | 3.00 D - 8                                                                        | -                                                                                  |              | 406        | 0           | 0          | LIP      |
| 18X7 - 8 (180/70 - 8)   | -     | -           |       | 4.33 R - 8                                                                        | -                                                                                  |              | 457        | 0           | 0          | LIP - NM |
| 16X6 - 8 (150/75 - 8)   | -     | -           |       | 4.33 R - 8                                                                        | -                                                                                  |              | 421        | 0           | 0          | LIP - NM |
| 4.00 - 8                | -     | -           | -     | 3.00 D - 8                                                                        | -                                                                                  |              | 406        | 0           | 0          | LIP - NM |
| 18X7 - 8 (180/70 - 8)   | -     | -           |       | 4.33 R - 8                                                                        | -                                                                                  |              | 457        | 0           | 0          | LIP      |
| 5.00 - 8                | -     | -           | -     | 3.00 D - 8                                                                        | -                                                                                  |              | 462        | 0           | 0          | STD - NM |
| 16X6 - 8 (150/75 - 8)   | -     | -           |       | 4.33 R - 8                                                                        | -                                                                                  |              | 421        | 0           | 0          | STD      |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026

| SIZE                    | TT/TL                 | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION  |
|-------------------------|-----------------------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|----------|
|                         |                       |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |          |
|                         |                       |             |       |  |  |              |            |             |            |          |
| 16X6 - 8 (150/75 - 8)   | -                     | -           |       | 4.33 R - 8                                                                        | -                                                                                  |              | 421        | 0           | 0          | STD - NM |
| 4.00 - 8                | -                     | -           | -     | 3.00 D - 8                                                                        | -                                                                                  |              | 406        | 0           | 0          | STD - NM |
| 4.00 - 8                | -                     | -           | -     | 3.00 D - 8                                                                        | -                                                                                  |              | 406        | 0           | 0          | STD      |
| 15X4.5 - 8 (125/75 - 8) | -                     | -           |       | 3.00 D - 8                                                                        | -                                                                                  |              | 378        | 0           | 0          | STD - NM |
| 18X7 - 8 (180/70 - 8)   | -                     | -           |       | 4.33 R - 8                                                                        | -                                                                                  |              | 457        | 0           | 0          | STD - NM |
| Ø9"                     | 6.00 - 9              | -           | -     | 4.00 E - 9                                                                        | -                                                                                  |              | 529        | 0           | 0          | LIP - NM |
|                         | 140/55 - 9            | -           | -     | 4.00 E - 9                                                                        | -                                                                                  |              | 377        | 0           | 0          | STD - NM |
|                         | 21X8 - 9 (200/75 - 9) | -           | -     | 6.00 E - 9                                                                        | -                                                                                  |              | 525        | 0           | 0          | STD      |
|                         | 140/55 - 9            | -           | -     | 4.00 E - 9                                                                        | -                                                                                  |              | 377        | 0           | 0          | STD      |
|                         | 140/55 - 9            | -           | -     | 4.00 E - 9                                                                        | -                                                                                  |              | 377        | 0           | 0          | LIP - NM |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026

| SIZE                 | TT/TL       | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION  |
|----------------------|-------------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|----------|
|                      |             |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |          |
|                      |             |             |       |  |  |              |            |             |            |          |
| 21X8 -9 (200/75 - 9) | -           | -           |       | 6.00 E - 9                                                                        | -                                                                                  |              | 525        | 0           | 0          | LIP - NM |
| 21X8 -9 (200/75 - 9) | -           | -           |       | 6.00 E - 9                                                                        | -                                                                                  |              | 525        | 0           | 0          | STD - NM |
| 6.00 - 9             | -           | -           | -     | 4.00 E - 9                                                                        | -                                                                                  |              | 529        | 0           | 0          | LIP      |
| 21X8 -9 (200/75 - 9) | -           | -           |       | 6.00 E - 9                                                                        | -                                                                                  |              | 525        | 0           | 0          | LIP      |
| 6.00 - 9             | -           | -           | -     | 4.00 E - 9                                                                        | -                                                                                  |              | 529        | 0           | 0          | STD - NM |
| 140/55 - 9           | -           | -           | -     | 4.00 E - 9                                                                        | -                                                                                  |              | 377        | 0           | 0          | LIP      |
| 6.00 - 9             | -           | -           | -     | 4.00 E - 9                                                                        | -                                                                                  |              | 529        | 0           | 0          | STD      |
| Ø10"                 | 6.50 - 10   | -           | -     | 5.00 F - 10                                                                       | -                                                                                  |              | 575        | 0           | 0          | LIP - NM |
|                      | 6.50 - 10   | -           | -     | 5.00 F - 10                                                                       | -                                                                                  |              | 575        | 0           | 0          | STD      |
|                      | 200/50 - 10 | -           | -     | 6.50 F - 10                                                                       | -                                                                                  |              | 458        | 0           | 0          | LIP - NM |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026

| SIZE                   | TT/TL | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION  |
|------------------------|-------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|----------|
|                        |       |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |          |
|                        |       |             |       |  |  |              |            |             |            |          |
| 200/50 - 10            | -     | -           | -     | 6.50 F - 10                                                                       | -                                                                                  |              | 458        | 0           | 0          | STD      |
| 180/60 - 10            | -     | -           | -     | 5.00F-10                                                                          | -                                                                                  |              | 460        | 0           | 0          | LIP      |
| 200/50 - 10            | -     | -           | -     | 6.50 F - 10                                                                       | -                                                                                  |              | 458        | 0           | 0          | LIP      |
| 180/60 - 10            | -     | -           | -     | 5.00F-10                                                                          | -                                                                                  |              | 460        | 0           | 0          | STD      |
| 200/50 - 10            | -     | -           | -     | 6.50 F - 10                                                                       | -                                                                                  |              | 458        | 0           | 0          | STD - NM |
| 6.50 - 10              | -     | -           | -     | 5.00 F - 10                                                                       | -                                                                                  |              | 575        | 0           | 0          | LIP      |
| 23X9 -10 (225/75 - 10) | -     | -           |       | 6.50 F - 10                                                                       | -                                                                                  |              | 585        | 0           | 0          | STD - NM |
| 23X9 -10 (225/75 - 10) | -     | -           |       | 6.50 F - 10                                                                       | -                                                                                  |              | 585        | 0           | 0          | LIP      |
| 23X9 -10 (225/75 - 10) | -     | -           |       | 6.50 F - 10                                                                       | -                                                                                  |              | 585        | 0           | 0          | LIP - NM |
| 23X9 -10 (225/75 - 10) | -     | -           |       | 6.50 F - 10                                                                       | -                                                                                  |              | 585        | 0           | 0          | STD      |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width O.O. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026

|      | SIZE                     | TT/TL | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION  |
|------|--------------------------|-------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|----------|
|      |                          |       |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |          |
|      |                          |       |             |       |  |  |              |            |             |            |          |
|      | 6.50 - 10                | -     | -           | -     | 5.00 F - 10                                                                       | -                                                                                  |              | 575        | 0           | 0          | STD - NM |
| Ø12" | 7.00 - 12                | -     | -           | -     | 5.00 S - 12                                                                       | -                                                                                  |              | 658        | 0           | 0          | LIP      |
|      | 27X10 - 12 (250/75 - 12) | -     | -           |       | 8.00 G - 12                                                                       | -                                                                                  |              | 677        | 0           | 0          | LIP - NM |
|      | 7.00 - 12                | -     | -           | -     | 5.00 S - 12                                                                       | -                                                                                  |              | 658        | 0           | 0          | STD      |
|      | 27X10 - 12 (250/75 - 12) | -     | -           |       | 8.00 G - 12                                                                       | -                                                                                  |              | 677        | 0           | 0          | LIP      |
|      | 315/45 - 12              | -     | -           | -     | 10.00G-12                                                                         | -                                                                                  |              | 578        | 0           | 0          | STD      |
|      | 27X10 - 12 (250/75 - 12) | -     | -           |       | 8.00 G - 12                                                                       | -                                                                                  |              | 677        | 0           | 0          | STD      |
|      | 315/45 - 12              | -     | -           | -     | 10.00G-12                                                                         | -                                                                                  |              | 578        | 0           | 0          | LIP      |
|      | 23X10 - 12 (250/60 - 12) | -     | -           |       | 8.00 G - 12                                                                       | -                                                                                  |              | 584        | 0           | 0          | LIP - NM |
|      | 7.00 - 12                | -     | -           | -     | 5.00 S - 12                                                                       | -                                                                                  |              | 658        | 0           | 0          | LIP - NM |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026

| SIZE                     | TT/TL                  | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION  |
|--------------------------|------------------------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|----------|
|                          |                        |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |          |
|                          |                        |             |       |  |  |              |            |             |            |          |
| 23X10 - 12 (250/60 - 12) | -                      | -           |       | 8.00 G - 12                                                                       | -                                                                                  |              | 584        | 0           | 0          | LIP      |
| 7.00 - 12                | -                      | -           | -     | 5.00 S - 12                                                                       | -                                                                                  |              | 658        | 0           | 0          | STD - NM |
| 27X10 - 12 (250/75 - 12) | -                      | -           |       | 8.00 G - 12                                                                       | -                                                                                  |              | 677        | 0           | 0          | STD - NM |
| 23X10 - 12 (250/60 - 12) | -                      | -           |       | 8.00 G - 12                                                                       | -                                                                                  |              | 584        | 0           | 0          | STD - NM |
| 23X10 - 12 (250/60 - 12) | -                      | -           |       | 8.00 G - 12                                                                       | -                                                                                  |              | 584        | 0           | 0          | STD      |
| Ø15"                     | 300 - 15 (315/70 - 15) | -           | -     | 8.0 - 15                                                                          | -                                                                                  |              | 820        | 0           | 0          | LIP      |
|                          | 7.50 - 15              | -           | -     | 5.5 - 15                                                                          | -                                                                                  |              | 756        | 0           | 0          | LIP      |
|                          | 7.00 - 15              | -           | -     | 5.5 - 15                                                                          | -                                                                                  |              | 730        | 0           | 0          | LIP      |
|                          | 7.50 - 15              | -           | -     | 5.5 - 15                                                                          | -                                                                                  |              | 756        | 0           | 0          | STD - NM |
|                          | 300 - 15 (315/70 - 15) | -           | -     | 8.0 - 15                                                                          | -                                                                                  |              | 820        | 0           | 0          | LIP - NM |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: O.O. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026



| SIZE                         | TT/TL | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION  |
|------------------------------|-------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|----------|
|                              |       |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |          |
|                              |       |             |       |  |  |              |            |             |            |          |
| 7.00 - 15                    | -     | -           |       | 5.5 - 15                                                                          | -                                                                                  |              | 730        | 0           | 0          | STD      |
| 7.50 - 15                    | -     | -           | -     | 6.0 - 15                                                                          | -                                                                                  |              | 756        | 0           | 0          | LIP - NM |
| 28X12.5 - 15 (355/45 - 15)   | -     | -           |       | 9.75 - 15                                                                         | -                                                                                  |              | 687        | 0           | 0          | STD      |
| 28X12.5 - 15 (355/45 - 15)   | -     | -           |       | 9.75 - 15                                                                         | -                                                                                  |              | 687        | 0           | 0          | STD - NM |
| 300 - 15 (315/70 - 15)       | -     | -           | -     | 8.0 - 15                                                                          | -                                                                                  |              | 820        | 0           | 0          | STD - NM |
| 7.50 - 15                    | -     | -           | -     | 6.0 - 15                                                                          | -                                                                                  |              | 756        | 0           | 0          | LIP      |
| 250 - 15 (250/70 - 15)       | -     | -           | -     | 7.0 - 15                                                                          | -                                                                                  |              | 718        | 0           | 0          | LIP - NM |
| 250 - 15 (250/70 - 15)       | -     | -           | -     | 7.0 - 15                                                                          | -                                                                                  |              | 718        | 0           | 0          | LIP      |
| 8.25 - 15                    | -     | -           | -     | 6.5 - 15                                                                          | -                                                                                  |              | 818        | 0           | 0          | LIP      |
| 32X12.5 - 15 (355 / 65 - 15) | -     | -           |       | 9.75 - 15                                                                         | -                                                                                  |              | 825        |             |            | LIP      |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026

| SIZE                           | TT/TL | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION  |
|--------------------------------|-------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|----------|
|                                |       |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |          |
|                                |       |             |       |  |  |              |            |             |            |          |
| 8.25 - 15                      | -     | -           | -     | 6.5 - 15                                                                          | -                                                                                  |              | 818        | 0           | 0          | STD      |
| 8.15 - 15 (28X9-15; 225/75-15) | -     | -           |       | 7.0 - 15                                                                          | -                                                                                  |              | 691        | 0           | 0          | STD - NM |
| 250 - 15 (250/70 - 15)         | -     | -           | -     | 7.0 - 15                                                                          | -                                                                                  |              | 718        | 0           | 0          | STD - NM |
| 7.50 - 15                      | -     | -           | -     | 5.5 - 15                                                                          | -                                                                                  |              | 756        | 0           | 0          | STD      |
| 5.50 - 15                      | -     | -           | -     | 4.50 E - 15                                                                       | -                                                                                  |              | 665        |             |            | STD      |
| 28X12.5 -15 (355/45 - 15)      | -     | -           |       | 9.75 - 15                                                                         | -                                                                                  |              | 687        | 0           | 0          | LIP      |
| 8.15 - 15 (28X9-15; 225/75-15) | -     | -           |       | 7.0 - 15                                                                          | -                                                                                  |              | 691        | 0           | 0          | LIP      |
| 28X12.5 -15 (355/45 - 15)      | -     | -           |       | 9.75 - 15                                                                         | -                                                                                  |              | 687        | 0           | 0          | LIP - NM |
| 300 - 15 (315/70 - 15)         | -     | -           | -     | 8.0 - 15                                                                          | -                                                                                  |              | 820        | 0           | 0          | STD      |
| 8.15 - 15 (28X9-15; 225/75-15) | -     | -           |       | 7.0 - 15                                                                          | -                                                                                  |              | 691        | 0           | 0          | LIP - NM |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026

| SIZE                           | TT/TL | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION  |
|--------------------------------|-------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|----------|
|                                |       |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |          |
|                                |       |             |       |  |  |              |            |             |            |          |
| 7.50 - 15                      | -     | -           | -     | 6.0 - 15                                                                          | -                                                                                  |              | 756        | 0           | 0          | STD - NM |
| 7.00 - 15                      | -     | -           |       | 5.5 - 15                                                                          | -                                                                                  |              | 730        | 0           | 0          | STD - NM |
| 32X12.5 - 15 (355 / 65 - 15)   | -     | -           |       | 9.75 - 15                                                                         | -                                                                                  |              | 825        |             |            | STD      |
| 8.25 - 15                      | -     | -           | -     | 6.5 - 15                                                                          | -                                                                                  |              | 818        | 0           | 0          | LIP - NM |
| 8.15 - 15 (28X9-15; 225/75-15) | -     | -           |       | 7.0 - 15                                                                          | -                                                                                  |              | 691        | 0           | 0          | STD      |
| 7.00 - 15                      | -     | -           |       | 5.5 - 15                                                                          | -                                                                                  |              | 730        | 0           | 0          | LIP - NM |
| 8.25 - 15                      | -     | -           | -     | 6.5 - 15                                                                          | -                                                                                  |              | 818        | 0           | 0          | STD - NM |
| 7.50 - 15                      | -     | -           | -     | 5.5 - 15                                                                          | -                                                                                  |              | 756        | 0           | 0          | LIP - NM |
| 7.50 - 15                      | -     | -           | -     | 6.0 - 15                                                                          | -                                                                                  |              | 756        | 0           | 0          | STD      |
| 250 - 15 (250/70 - 15)         | -     | -           | -     | 7.0 - 15                                                                          | -                                                                                  |              | 718        | 0           | 0          | STD      |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%—S.W. 2%—RC 2.5%—LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026

|      | SIZE        | TT/TL | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION |
|------|-------------|-------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|---------|
|      |             |       |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |         |
|      |             |       |             |       |  |  |              |            |             |            |         |
| NEW  | 355/50 - 15 | -     | -           |       | 9.75 - 15                                                                         | -                                                                                  |              | 721        | 0           | 0          | STD     |
|      | 355/50 - 15 | -     | -           |       | 9.75 - 15                                                                         | -                                                                                  |              | 721        | 0           | 0          | LIP     |
|      | 7.00 - 15   | -     | -           |       | 6.0 - 15                                                                          | -                                                                                  |              | 730        | 0           | 0          | STD     |
| Ø20" | 12.00 - 20  | -     | -           | -     | 8.50 - 20                                                                         | -                                                                                  |              | 1090       |             |            | STD     |
|      | 10.00 - 20  | -     | -           | -     | 7.50 - 20                                                                         | -                                                                                  |              | 1035       |             |            | STD     |
|      | 10.00 - 20  | -     | -           | -     | 8.00 - 20                                                                         | -                                                                                  |              | 1035       |             |            | STD     |
|      | 10.00 - 20  | -     | -           | -     | 7.00 - 20                                                                         | -                                                                                  |              | 1035       |             |            | STD     |
|      | 11.00 - 20  | -     | -           | -     | 8.00 - 20                                                                         | -                                                                                  |              | 1060       |             |            | STD     |
|      | 9.00 - 20   | -     | -           | -     | 7.00 - 20                                                                         | -                                                                                  |              | 990        |             |            | STD     |
|      | 12.00 - 20  | -     | -           | -     | 8.00 - 20                                                                         | -                                                                                  |              | 1090       |             |            | STD     |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0, outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Balkrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 29/07/2026

| SIZE        | TT/TL | STAR RATING | LI/SS | RIM                                                                               |                                                                                    | O.W.<br>(mm) | OD<br>(mm) | SLR<br>(mm) | RC<br>(mm) | VERSION |
|-------------|-------|-------------|-------|-----------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------|------------|-------------|------------|---------|
|             |       |             |       | REC RIM                                                                           | ALT RIM                                                                            |              |            |             |            |         |
|             |       |             |       |  |  |              |            |             |            |         |
| 9.00 - 20   | -     | -           | -     | 6.50 - 20                                                                         | -                                                                                  |              | 990        |             |            | STD     |
| 11.00 - 20  | -     | -           | -     | 7.50 - 20                                                                         | -                                                                                  |              | 1060       |             |            | STD     |
| <b>Ø24"</b> |       |             |       |                                                                                   |                                                                                    |              |            |             |            |         |
| 14.00 - 24  | -     | -           | -     | 10.00 - 24                                                                        | -                                                                                  |              | 1320       |             |            | STD     |

LIP: LIP, STD: STANDARD, LIP - NM: LIP - NON MARKING, STD - NM: STANDARD - NON MARKING

| TECHNOLOGIES                                                                        |                                                                                     | PERFORMANCES                                                                        |                                                                                     |
|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------|
|  |  |  |  |
|  |  |  |  |
| -                                                                                   | -                                                                                   |                                                                                     |                                                                                     |

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tire width 0.0. outer diameter of the tire: SLR static radius, RC rolling circumference ; SRI index