

# AGRIMAX RT 855

<b>TIRE SIZE</b>	<b>320/85 R 36</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	
<b>MACHINERY</b>	SPRAYER / VINEYARD HARVESTER / TRACTOR / HARVESTER / IMPLEMENTS
<b>VERSION</b>	STANDARD
<b>TL/TT</b>	TL
<b>LI/SS</b>	147 D ; 150 A8



## DIMENSIONS US STANDARD

<b>USA CODE</b>	94052691	<b>RC (IN)</b>	173.4
<b>SW (IN)</b>	13.0	<b>RIM REC</b>	W 11
<b>OD (IN)</b>	57.4	<b>RIM ALT</b>	W 9 ; W 10
<b>SLR (IN)</b>	26.5	<b>ECE</b>	E11-106R-003511

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	12	15	17	23	29	35	41	46	52	58	64
45	2560	2930	3310	3990	4430	4670	5110	5540	5920	6230	6780
30	2690	3090	3470	4200	4650	4920	5380	5830	6230	6550	7120
25	2800	3210	3630	4380	4850	5130	5600	6070	6490	6820	7390
20	2940	3370	3800	4590	5090	5380	5870	6380	6810	7160	7800
5 LT	3430	3940	4430	5360	5940	6270	6860	7440	7950	8360	9090
5 HT	2940	3370	3800	4590	5090	5380	5870	6380	6810	7160	7800

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.