


AGRIMAX RT 855

TIRE SIZE	480/80 R 42
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	PULVERIZATOR / MAȘINĂ DE RECOLTAT PODGORII / TRACTOR / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	151 A8/B



DIMENSIUNI US STANDARD

USA CODE	94021796	RC (IN)	216.3
SW (IN)	18.9	RIM REC	W 16 A; DD 16; DW 16 A
OD (IN)	72.2	RIM ALT	DD 16 L; DW 16 L; W 16 L
SLR (IN)	32.9	ECE	E4-106R-000791

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23
30	4190	4870	5560	6240	6920	7600
25	4190	4870	5560	6240	6920	7600
20	4490	5210	5950	6680	7420	8150
5 LT	5610	6530	7450	8370	9280	10200
5 HT	4490	5210	5950	6680	7420	8150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.