


RIB 713

| | |
|---------------------|--|
| TIRE SIZE | IF 280/70 R 15 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IMPLEMENT MACHINERY / IMPLEMENTS |
| VERSION | STUBBLE RESISTANT |
| TIRE TYPE | TL |
| LI/SS | 128 D |



DIMENSIONS US STANDARD

| | | | |
|-----------------|----------|-----------------|----------------|
| USA CODE | 94046201 | RC (IN) | 92.8 |
| SW (IN) | 11.0 | RIM REC | W 8 |
| OD (IN) | 30.7 | ECE | E4-106R-001820 |
| SLR (IN) | 13.7 | TRA CODE | I1 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 | 41 | 46 | 52 |
|-------------------------|------|------|------|------|------|------|------|------|------|------|------|
| FROM 5 TO 40 MPH | 1480 | 1710 | 1950 | 2230 | 2470 | 2700 | 2940 | 3140 | 3460 | 3740 | 3970 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.