

# CON STAR

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | 400/70 - 24  |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> | ❖ BIAS   |
| <b>MACHINERY</b>    | CARREGADORA COMPACTA /<br>LEVANTADOR TElescÓPICO /<br>CARREGADORA COMPACTA /<br>LEVANTADOR TElescÓPICO |
| <b>VERSÃO</b>       | INDUSTRIAL   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 158 A8   |



## DIMENSÕES US STANDARD

|                   |          |                |   |
|-------------------|----------|----------------|---|
| <b>CÓDIGO USA</b> | 94051977 | <b>RC (IN)</b> | 140.0                                     |
| <b>SW (IN)</b>    | 15.6     | <b>RIM REC</b> | 13  |
| <b>OD (IN)</b>    | 46.3     | <b>RIM ALT</b> | DW 12; 13 SDC; DW 13; DW 13 L;<br>DW 14 L |
| <b>SLR (IN)</b>   | 21.4     | <b>ECE</b>     | E11-106R-003025                           |

## LOAD CAPACITY (LBS/TIRE)

|                  |           |
|------------------|-----------|
| <b>MPH / PSI</b> | <b>73</b> |
| 25               | 9370      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.