

# FARM 2000

<b>TIRE SIZE</b>	<b>250/80 - 16</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	ТРАКТОР-ТЯГАЧ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	113 A8
<b>LI/SS FREE ROLLING</b>	125 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94513574	<b>RC (IN)</b>	95.6
<b>SW (IN)</b>	9.4	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	32.3	<b>RIM ALT</b>	W 7; W 9; W 8 L
<b>SLR (IN)</b>	14.5	<b>ECE</b>	E11-106R-003518

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	41
5 FR	5090
15 FR	4330
20 FR	4080
25 FR	3640
5 DW	3550
15 DW	3020
20 DW	2840
25 DW	2540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.