


# FL 630 ULTRA

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>560/45 R 22.5</b>   |
| <b>UM</b>           | US STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | MAȘINĂ DE ÎMPRĂȘTIAT / CISTERNĂ /<br>REMORCĂ / MAȘINI DE<br>IMPLEMENTARE                 |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 152 D ; 163 A8   |



## DIMENSIUNI US STANDARD

|                 |          |                |                 |
|-----------------|----------|----------------|-----------------|
| <b>USA CODE</b> | 94052790 | <b>RC (IN)</b> | 129.5           |
| <b>SW (IN)</b>  | 21.4     | <b>RIM REC</b> | AG 16.00        |
| <b>OD (IN)</b>  | 42.4     | <b>ECE</b>     | E11-106R-003012 |
| <b>SLR (IN)</b> | 19.3     |                |                 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 12   | 15   | 17   | 23   | 29   | 35   | 41    | 46    | 52    | 58    |
|-----------|------|------|------|------|------|------|-------|-------|-------|-------|
| 45        | 2290 | 2610 | 2930 | 3640 | 4140 | 4780 | 5420  | 5930  | 6490  | 7130  |
| 40        | 2510 | 2870 | 3220 | 4000 | 4540 | 5250 | 5950  | 6500  | 7130  | 7830  |
| 30        | 3040 | 3470 | 3890 | 4840 | 5500 | 6360 | 7210  | 7870  | 8630  | 9480  |
| 25        | 3440 | 3920 | 4410 | 5490 | 6240 | 7210 | 8170  | 8930  | 9790  | 10750 |
| 20        | 3790 | 4320 | 4850 | 6040 | 6870 | 7930 | 8990  | 9820  | 10770 | 11830 |
| 15        | 3970 | 4530 | 5080 | 6320 | 7180 | 8290 | 9400  | 10270 | 11260 | 12370 |
| 5         | 4510 | 5150 | 5780 | 7190 | 8180 | 9450 | 10710 | 11690 | 12820 | 14090 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.