

AGRIMAX V-FLECTO

TYRE SIZE	VF 420/85 R 34
UM	IS STANDARD
MACHINERY	HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	159 E



DIMENSIONS IS STANDARD

SW (MM)	439	RIM REC	W 15
OD (MM)	1580	ECE	E11-106R-0012140
SLR (MM)	711	SRI	750
RC (MM)	4731		

LOAD CAPACITY (KG/TYRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
70	2060	2365	2715	3065	3415	3765	4115	4375
FROM 65 TO 40	2060	2365	2715	3065	3415	3765	4115	4375
30	2095	2405	2765	3120	3475	3835	4190	4460
20	2135	2455	2820	3185	3545	3910	4275	4550
10	2260	2595	2980	3365	3750	4135	4520	4810
*UPTO 10 CYC WITH FRONT LOADER	3050	3505	4025	4545	5065	5585	6105	6495
10HT	2095	2405	2765	3120	3475	3835	4190	4460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.