



IS standard



GROWING TOGETHER

# FLOTATION 351



PRODUCT DATA SHEET



Bias



Performance



High Load Capacity



Durability



Traction



# FLOTATION 351

FLOTATION 351 is a bias flotation tire which best suits transport applications using trailers. Extra deep lugs provide outstanding traction and a longer tire life. FLOTATION 351 is the ideal tire on wet and moist surfaces ensuring high load capacity.

	Tire size	RIM		S.W. (mm)	O.D. (mm)	SLR (mm)	RC (mm)	Version	PR	Type	LI/SS
		Rec.	Alt.								
Ø 20"	42 X 25.00 - 20	20.50 HF	20.50 VF	605	1110	508	3302	STD	12	TL	135 B
	42 X 25.00 - 20	20.50 HF	20.50 VF	605	1110	508	3302	STD	16	TL	139 B
	48 X 25.00 - 20	20.50 HF	20.50 VF	630	1270	559	3785	STD	10	TL	144 B
	48 X 31.00 - 20	26.00 HF	26.00 VF	775	1283	559	3886	STD	12	TL	148 B
Ø 25"	66 X 43.00 - 25	36.0 TH	-	1020	1750	782	5213	STD	6	TL	150 B
	66 X 43.00 - 25	36.0 TH	-	1020	1750	782	5213	STD	10	TL	160 B
	66 X 43.00 - 25	36.0 TH	-	1020	1750	782	5213	STD	16	TL	170 B

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference