

AGRIMAX RT 955

TIRE SIZE	300/95 R 46
UM	US STANDARD
MACHINERY	PULVÉRISATEUR / MACHINE À VENDANGER / MOISSONNEUSE / OUTILLAGE AGRICOLE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	148 A8/B



DIMENSIONS US STANDARD

CODE USA	94021871	RC (IN)	209.4
SW (IN)	11.6	RIM REC	W 9
OD (IN)	68.4	RIM ALT	W 10 ; W 11 ; DW 10 ; DW 11
SLR (IN)	32.0	ECE	E4-106R-000790

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52	58	64
30	2440	2850	3270	3680	4100	4450	4860	5210	5700	6180	6600	6950	-
25	2440	2850	3270	3680	4100	4450	4860	5210	5700	6180	6600	6950	-
20	2610	3050	3510	3950	4400	4760	5210	5590	6110	6620	7080	7440	-
10	3000	3510	4020	4530	5050	5470	5990	6420	7010	7610	8120	8540	-
5	3360	3940	4510	5090	5670	6140	6710	7200	7870	8540	9120	9590	10420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.