


# MULTIMAX MP 527

|                     |  |
|---------------------|--|
| <b>TIRE SIZE</b>    | <b>480/80 R 26 IND</b>   |
| <b>UM</b>           | IS STANDARD  |
| <b>CONSTRUCTION</b> |  RADIAL |
| <b>MACHINERY</b>    | KOMPAKTHJULLASTARE /<br>TELESKOPLASTARE /<br>KOMPAKTHJULLASTARE /<br>TELESKOPLASTARE     |
| <b>VERSION</b>      | STANDARD   |
| <b>TIRE TYPE</b>    | TL   |
| <b>LI/SS</b>        | 160 A8/B   |



## DIMENSIONER IS STANDARD

|                 |      |                |                 |
|-----------------|------|----------------|-----------------|
| <b>SW (MM)</b>  | 479  | <b>RIM REC</b> | DW 15 L         |
| <b>OD (MM)</b>  | 1428 | <b>RIM ALT</b> | DW 16 L         |
| <b>SLR (MM)</b> | 642  | <b>ECE</b>     | E11-106R-004069 |
| <b>RC (MM)</b>  | 4259 | <b>SRI</b>     | 675             |

## LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.6  | 2.0  | 2.2  | 2.4  | 2.6  | 2.8  | 3.2  | 3.2  | 3.4  | 3.6   |
|------------|------|------|------|------|------|------|------|------|------|-------|
| 50         | 2610 | 3060 | 3330 | 3555 | 3780 | 4005 | 4275 | 4500 | -    | -     |
| 40         | 2610 | 3060 | 3330 | 3555 | 3780 | 4005 | 4275 | 4500 | -    | -     |
| 30         | 2795 | 3275 | 3565 | 3805 | 4045 | 4290 | 4575 | 4815 | -    | -     |
| 25         | 2900 | 3400 | 3700 | 3950 | 4200 | 4450 | 4750 | 4995 | -    | -     |
| 10 CYC.    | 3175 | 3915 | 4255 | 4590 | 4995 | 5335 | 5670 | 6075 | 6415 | 6750  |
| STATIC     | 4865 | 6005 | 6525 | 7040 | 7660 | 8180 | 8695 | 9315 | 9835 | 10350 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.