


# AGRIMAX SPARGO

<b>TYRE SIZE</b>	<b>VF 380/90 R 54</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRACTOR
<b>VERSION</b>	STANDARD
<b>TYRE TYPE</b>	TL
<b>LI/SS</b>	176 D



## DIMENSIONS IS STANDARD

<b>SW (MM)</b>	383	<b>RIM REC</b>	W13
<b>OD (MM)</b>	2056	<b>RIM ALT</b>	DW 13; DW 12; W 12
<b>SLR (MM)</b>	948	<b>ECE</b>	E11-106R-0010081
<b>RC (MM)</b>	6232	<b>SRI</b>	975

## LOAD CAPACITY (KG/TYRE)

KM/H / BAR	1.0	1.2	1.4	1.6	1.8	2.0	2.2	2.4	2.6	2.8	3.0	3.2	3.4	3.6	3.8	4.0	4.2	4.4
<b>70</b>	2825	3155	3550	3875	4075	4270	4400	5430	4760	4990	5190	5385	5550	5715	5880	6040	6305	6565
<b>FROM 65 TO 40</b>	3055	3410	3835	4190	4405	4615	4760	4900	5150	5400	5610	5825	6000	6180	6355	6535	6820	7100
<b>30</b>	3120	3480	3915	4275	4495	4710	4855	5000	5255	5510	5725	5945	6125	6305	6485	6670	6960	7245
<b>20</b>	3180	3545	3990	4360	4580	4805	4950	5100	5355	5615	5835	6060	6245	6425	6610	6795	7090	7385
<b>10</b>	3360	3750	4220	4610	4845	5080	5235	5390	5665	5940	6170	6405	6600	6795	6990	7190	7500	7810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.