

# AGRIMAX V-FLECTO

|              |                                                                                          |
|--------------|------------------------------------------------------------------------------------------|
| TYRE SIZE    | VF 900/65 R 46                                                                           |
| UM           | US STANDARD                                                                              |
| CONSTRUCTION |  RADIAL |
| MACHINERY    | HIGH-POWER TRACTOR / TRACTOR                                                             |
| VERSION      | STEEL BELTED                                                                             |
| TL/TT        | TL                                                                                       |
| LI/SS        | 193 D                                                                                    |



## DIMENSIONS US STANDARD

|          |          |         |                  |
|----------|----------|---------|------------------|
| USA CODE | 94512690 | RC (IN) | 275.7            |
| SW (IN)  | 35.4     | RIM REC | DW 30B           |
| OD (IN)  | 92.0     | ECE     | E11-106R-0010961 |
| SLR (IN) | 39.6     |         |                  |

## LOAD CAPACITY (LBS/TYRE)

| MPH / PSI                     | 9     | 12    | 15    | 17    | 20    | 23    | 29    |
|-------------------------------|-------|-------|-------|-------|-------|-------|-------|
| 45                            | 11760 | 13600 | 15450 | 17530 | 19150 | 20760 | 23070 |
| FROM 40 TO 25                 | 12930 | 14960 | 16990 | 19270 | 21040 | 22820 | 25350 |
| 20                            | 13180 | 15260 | 17320 | 19640 | 21460 | 23270 | 25860 |
| 12                            | 13440 | 15550 | 17660 | 20030 | 21880 | 23720 | 26370 |
| 5                             | 14220 | 16450 | 18680 | 21190 | 23140 | 25100 | 27890 |
| *UPTO 5 CYC WITH FRONT LOADER | 18110 | 20945 | 23790 | 26985 | 29465 | 31945 | 35495 |
| 5 HT                          | 13180 | 15260 | 17320 | 19640 | 21460 | 23270 | 25860 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.