

# AGRIMAX RT 657

<b>TIRE SIZE</b>	<b>650/65 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / ТРАКТОР-ТЯГАЧ / КОМБАЙН
<b>VERSION</b>	STEEL BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	178 A8 ; 175 B



## РАЗМЕРЫ IS STANDARD

<b>SW (MM)</b>	645	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1816	<b>RIM ALT</b>	DW 21 B; DW 23 B
<b>SLR (MM)</b>	827	<b>ECE</b>	E11-106R-008886
<b>RC (MM)</b>	5488	<b>SRI</b>	875

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	3.5
50	6900
40	7500
30	8030
25	8330
10	11250
STATIC	17250
10 LT	10500
20 LT	9000
10 HT	8030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.