


AGRIMAX RT 855

| | |
|---------------------|--|
| TIRE SIZE | 210/95 R 20 |
| UM | US STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | IRRORAZIONE / VENDEMMIATRICE / TRATTORE / MIETITREBBIA / ATTREZZI AGRICOLI |
| VERSIONE | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 110 A8/B |



DIMENSIONI US STANDARD

| | | | |
|-------------------|----------|----------------|----------------|
| CODICE USA | 94043804 | RC (IN) | 108.2 |
| SW (IN) | 8.4 | RIM REC | W 7 |
| OD (IN) | 35.7 | RIM ALT | W 6 |
| SLR (IN) | 16.5 | ECE | E4-106R-000637 |

LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 9 | 12 | 15 | 17 | 20 | 23 | 29 | 35 |
|-------------|------|------|------|------|------|------|------|------|
| 30 | 1100 | 1270 | 1450 | 1640 | 1830 | 2020 | 2180 | 2340 |
| 25 | 1100 | 1270 | 1450 | 1640 | 1830 | 2020 | 2180 | 2340 |
| 20 | 1180 | 1360 | 1550 | 1750 | 1960 | 2160 | 2340 | 2500 |
| 5 LT | 1480 | 1700 | 1950 | 2200 | 2460 | 2710 | 2930 | 3140 |
| 5 HT | 1180 | 1360 | 1550 | 1750 | 1960 | 2160 | 2340 | 2500 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.