


# AT 171

<b>TIRE SIZE</b>	<b>35X9 - 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ATV / TRACTOR PENTRU MUD BOGGER / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TT
<b>LI/SS</b>	85 A8 ; 61 F



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	200	<b>RIM REC</b>	W 7
<b>OD (MM)</b>	895	<b>RIM ALT</b>	W 6
<b>SLR (MM)</b>	419	<b>PR</b>	6
<b>RC (MM)</b>	2670	<b>TRA CODE</b>	R1W+

## LOAD CAPACITY (KG/TIRE)

<b>KM/H / BAR</b>	<b>1.40</b>	<b>1.00</b>
<b>40 MUD BOGGING</b>	515	-
<b>80 MUD BOGGING</b>	257	-
<b>40 CASUAL TRANSPORT</b>	-	425
<b>80 CASUAL TRANSPORT</b>	-	218

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.