

# AW 708

**19.0/45 - 17**

|                     |   |
|---------------------|---|
| <b>UM</b>           | US STANDARD   |
| <b>CONSTRUCTION</b> | ❖ BIAS  |
| <b>MACHINERY</b>    | BALYA MAKINESI / UYGULAMALI<br>MAKINE / RÖMORK / BIÇERDÖVER /<br>UYGULAMALI MAKINE / RÖMORK |
| <b>VERSION</b>      | STANDARD  |
| <b>TIRE TYPE</b>    | TL  |
|                     | 138 A8  |



## UNDEFINED US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94010233 | <b>RC (IN)</b> | 99.8           |
| <b>SW (IN)</b>  | 18.5     | <b>RIM REC</b> | 16.00          |
| <b>OD (IN)</b>  | 34.1     | <b>ECE</b>     | E4-106R-002334 |
| <b>SLR (IN)</b> | 15.0     | <b>PR</b>      | 10             |

## LOAD CAPACITY (LBS/TIRE)

| <b>MPH / PSI</b> | <b>33</b> |
|------------------|-----------|
| <b>5 FR</b>      | 7290      |
| <b>15 FR</b>     | 6190      |
| <b>20 FR</b>     | 5830      |
| <b>25 FR</b>     | 5200      |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.