


AGRIMAX RT 600

TIRE SIZE	750/70 R 26
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	MAȘINĂ DE RECOLTARE / MAȘINĂ DE ÎMPRĂȘTIAT / TRACTOR / MAȘINI DE IMPLEMENTARE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	172 A8/B



DIMENSIUNI IS STANDARD

SW (MM)	780	RIM REC	DW 25 B
OD (MM)	1750	RIM ALT	DW 24 B
SLR (MM)	785	ECE	E11-106R-007934
RC (MM)	5269	SRI	825

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2	3.6
50	2710	3150	3595	4035	4475	4915	5420	5735	6300	-	-
40	2710	3150	3595	4035	4475	4915	5420	5735	6300	-	-
30	2905	3375	3850	4320	4795	5265	5805	6145	6750	-	-
10 LT	3635	4225	4820	5410	6000	6595	7270	7690	8450	-	-
10 HT	2905	3375	3850	4320	4795	5265	5805	6145	6750	-	-
10 CYC	-	5065	5775	6480	7190	7900	8710	9215	10125	10285	10710

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.