


# AGRIMAX RT 955

<b>TIRE SIZE</b>	<b>300/95 R 46</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZADOR AGRÍCOLA / VINDIMADORA / CEIFEIRA / IMPLEMENTOS AGRÍCOLAS
<b>VERSÃO</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	148 A8/B



## DIMENSÕES US STANDARD

<b>CÓDIGO USA</b>	94021871	<b>RC (IN)</b>	209.4
<b>SW (IN)</b>	11.6	<b>RIM REC</b>	W 9
<b>OD (IN)</b>	68.4	<b>RIM ALT</b>	W 10; W 11; DW 10; DW 11
<b>SLR (IN)</b>	32.0	<b>ECE</b>	E4-106R-000790

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35	41	46	52	58	64
30	2440	2850	3270	3680	4100	4450	4860	5210	5700	6180	6600	6950	-
25	2440	2850	3270	3680	4100	4450	4860	5210	5700	6180	6600	6950	-
20	2610	3050	3510	3950	4400	4760	5210	5590	6110	6620	7080	7440	-
10	3000	3510	4020	4530	5050	5470	5990	6420	7010	7610	8120	8540	-
5	3360	3940	4510	5090	5670	6140	6710	7200	7870	8540	9120	9590	10420

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.