

AGRIMAX FORCE

TIRE SIZE	IF 600/70 R 34
UM	US STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	HARVESTER / HIGH-POWER TRACTOR / TRACTOR
VERSION	STANDARD
TL/TT	TL
LI/SS	167 D



DIMENSIONS US STANDARD

USA CODE	94045228	RC (IN)	199.6
SW (IN)	23.7	RIM REC	DW 21 B ; DW 21 A
OD (IN)	67.1	RIM ALT	DW 20 A ; DW 20 B
SLR (IN)	29.8	ECE	E4-106R-001408

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	5130	5900	6770	7650	8520	9390	10260	10920
FROM 40 TO 25	5640	6480	7440	8410	9370	10330	11290	12000
20	5860	6730	7740	8740	9740	10740	11730	12490
12	6080	7000	8040	9080	10120	11140	12180	12970
5	7160	8220	9450	10680	11890	13110	14330	15260
*UPTO 5 CYC WITH FRONT LOADER	7890	9070	10420	11770	13120	14450	15800	16820
5 HT	5860	6730	7740	8740	9740	10740	11730	12490

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.