

# RIB 774 (C)

<b>TIRE SIZE</b>	<b>19.0/45 - 17</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 BIAS
<b>MACHINERY</b>	ПРЕСС-ПОДБОРЩИК / КОМБАЙН / ПРИЦЕП / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	138 A8



## РАЗМЕРЫ US STANDARD

<b>USA CODE</b>	94027330	<b>RC (IN)</b>	99.1
<b>SW (IN)</b>	17.9	<b>RIM REC</b>	16.00
<b>OD (IN)</b>	33.3	<b>ECE</b>	E11-106R-004589
<b>SLR (IN)</b>	15.2	<b>PR</b>	10

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	33
5 FR	7290
15 FR	6190
20 FR	5830
25 FR	5200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.