

# FLOTATION V LINE

<b>TIRE SIZE</b>	<b>500/60 - 22.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	❖ BIAS
<b>MACHINERY</b>	REMORCĂ / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS DRIVE WHEEL</b>	145 A8/142 B
<b>LI/SS FREE ROLLING</b>	157 A8/154 B



## DIMENSIUNI US STANDARD

<b>USA CODE</b>	94006205	<b>RC (IN)</b>	137.4
<b>SW (IN)</b>	19.7	<b>RIM REC</b>	AG 16.00
<b>OD (IN)</b>	46.1	<b>RIM ALT</b>	15.00; 17.00
<b>SLR (IN)</b>	20.1	<b>ECE</b>	E4-106R-001561

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	22	29	35
<b>5 FR</b>	9680	11450	12730
<b>10 FR</b>	8710	10310	11460
<b>20 FR</b>	7740	9160	10180
<b>25 FR</b>	6910	8180	9090
<b>30 FR</b>	6220	7360	8270
<b>5 DW</b>	6800	8040	8950
<b>10 DW</b>	6130	7230	8060
<b>20 DW</b>	5450	6440	7160
<b>25 DW</b>	4860	5740	6390
<b>30 DW</b>	4380	5170	5840

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.