

AS 504

TIRE SIZE	10.5/80 - 18
UM	US STANDARD
CONSTRUCTION	⊠ BIAS
MACHINERY	ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК / ПРИЦЕП ДЛЯ ПОЛЕВЫХ РАБОТ / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ / ТЕЛЕСКОПИЧЕСКИЙ ПОГРУЗЧИК
VERSION	STANDARD
TIRE TYPE	TL
LI/SS DRIVE WHEEL	119 A8
LI/SS FREE ROLLING	131 A8



РАЗМЕРЫ US STANDARD

USA CODE	94018628	RC (IN)	105.2
SW (IN)	10.8	RIM REC	W 9
OD (IN)	35.7	RIM ALT	9; W 8
SLR (IN)	16.9	ECE	E4-106R-002325

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	54
5 FR	6020
15 FR	5110
20 FR	4820
25 FR	4300
5 DW	4200
15 DW	3570
20 DW	3360
25 DW	3000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.