


FL 639

850/40 R 26.5

UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	YAYICI / UYGULAMALI MAKINE
VERSION	STANDARD
TIRE TYPE	TL
	173 D ; 184 A8



UNDEFINED IS STANDARD

SW (MM)	860	RIM REC	AG 28.00
OD (MM)	1355	ECE	E11-106R-006228
SLR (MM)	599	SRI	650
RC (MM)	4122		

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.8	1.2	1.6	2.0	2.4	2.8	3.2	3.6	4.0
70	1895	2430	3020	3435	3965	4500	4910	5385	5915
65	2080	2665	3315	3770	4355	4940	5395	5915	6500
50	2520	3225	4015	4565	5270	5980	6530	7160	7865
40	2880	3690	4590	5220	6030	6840	7470	8190	9000
30	3145	4025	5010	5695	6580	7460	8150	8935	9815
25	3290	4215	5240	5960	6885	7810	8525	9350	10270
10	3745	4800	5970	6790	7840	8895	9715	10650	11700

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.