


# AGRIMAX V-FLECTO

<b>TIRE SIZE</b>	<b>VF 600/60 R 38</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	HOCHLEISTUNGSTRAKTOR / TRACTOR
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	166 D



## ABMESSUNGEN IS STANDARD

<b>SW (MM)</b>	587	<b>RIM REC</b>	DW 20 B
<b>OD (MM)</b>	1685	<b>RIM ALT</b>	DW 18 L
<b>SLR (MM)</b>	757	<b>ECE</b>	E11-106R-005021
<b>RC (MM)</b>	5081	<b>SRI</b>	800

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2360	2745	3180	3565	3950	4340	4820
<b>FROM 65 TO 40</b>	2595	3020	3495	3920	4345	4770	5300
30	2645	3080	3560	3995	4430	4865	5405
20	2695	3140	3630	4075	4515	4960	5510
10	2850	3320	3840	4310	4775	5245	5830
<b>*UPTO 10 CYC WITH FRONT LOADER</b>	3630	4225	4890	5485	6080	6675	7420
10HT	2645	3080	3560	3995	4430	4865	5405

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.