

AGRIMAX RT 657



AGRIMAX
RADIAL TRACTOR TIRES

AGRIMAX RT 657



AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.



	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø16"	320/65 R 16	117 D 120 A8	W 10	W 9 W 11	319	822	366	2466	390	STD
Ø18"	340/65 R 18	113 A8/B	W 11	W 10 W 12	343	899	400	2667	425	STD
	320/65 R 18	125 A8/B	W 10	W 9 W 11	310	885	400	2667	425	STD
	320/65 R 18	109 A8/B	W 10	W 9 W 11	319	873	392	2587	425	STD
Ø20"	420/65 R 20	135 D 138 A8	W 13	W 11 W 12	418	1054	468	3162	500	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			
			
			
Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference, SRI index			

	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
	440/65 R 20	138 D 141 A8	W 14 L	W 13 W 15 L	441	1080	479	3240	525	STD
	340/65 R 20	124 D 127 A8	W 11	W 10 W 12	343	950	430	2892	450	STD
Ø24"	440/65 R 24	135 D 138 A8	W 14 L	W 13 W 15 L	441	1182	538	3546	575	STD
	480/65 R 24	140 D 143 A8	W 15 L	W 14 L	479	1234	562	3730	600	SPL
	540/65 R 24	146 D 149 A8	W 16 L	W 18 L	530	1312	596	3942	625	STD
	540/65 R 24	146 D 149 A8	W 16 L	W 18 L	530	1312	590	3930	625	SPL
	440/65 R 24	135 D 138 A8	W 14 L	W 13 W 15 L	441	1182	538	3546	575	SPL
	420/65 R 24	138 D 141 A8	W 13	W 11 W 12	418	1156	519	3468	550	STD
	480/65 R 24	140 D 143 A8	W 15 L	W 14 L	479	1234	562	3730	600	STD
Ø28"	540/65 R 28	149 D 152 A8	W 16 L	W 18 L	530	1413	643	4253	675	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			
			
D	181 kg		

Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
480/65 R 28	142 D 145 A8	W 15 L	W 14 L	479	1335	610	4091	650	STD
600/65 R 28	154 D 157 A8	DW 20 B	W 18 L	611	1491	670	4470	700	STD
420/65 R 28	135 D 138 A8	W 13	W 12 W 11	418	1257	584	3824	600	STD
540/65 R 28	149 D 152 A8	W 16 L	W 18 L	530	1413	643	4253	675	SPL
440/65 R 28	138 D 141 A8	W 14 L	W 13 W 15 L	441	1283	590	3927	625	STD
600/65 R 28	154 D 157 A8	DW 20 B	W 18 L	611	1491	670	4470	700	SPL
540/65 R 30	150 D 153 A8	W 16 L	W 18 L	530	1464	670	4403	700	SPL
420/65 R 30	136 D 139 A8	W 13	W 12 W 11	418	1308	606	3952	625	STD
600/65 R 30	155 D 158 A8	DW 20 B	W 18 L	611	1542	697	4609	725	STD
540/65 R 30	150 D 153 A8	W 16 L	W 18 L	530	1464	670	4403	700	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			
			
D	181 kg		

Permissible tolerances: 0.0. 2%-S.W. 2%-RC 2.5%-LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index

	SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
			REC RIM	ALT RIM						
										
Ø34"	540/65 R 34	152 D 155 A8	W 16 L	W 18 L	530	1566	712	4742	750	SPL
	540/65 R 34	152 D 155 A8	W 16 L	W 18 L	530	1566	712	4742	750	STD
	600/65 R 34	157 D 160 A8	DW 20 B	W 18 L	611	1644	742	4960	775	STD
	600/65 R 34	157 D 160 A8	DW 20 B	W 18 L	611	1644	742	4960	775	SPL
Ø38"	540/65 R 38	153 D 156 A8	W 16 L	W 18 L	530	1667	760	5059	800	SPL
	600/65 R 38	159 D 162 A8	DW 20 B	W 18 L	611	1745	790	5247	825	SPL
	650/65 R 38	163 D 166 A8	DW 20 B	DW 21 B DW 23 B	645	1811	830	5483	875	STD
	650/65 R 38	163 D 166 A8	DW 20 B	DW 21 B DW 23 B	645	1811	830	5483	875	SPL
	900/55 R 38	179 D 181 A8	DW 27 B	DW 30 B	880	1950	880	5842	925	STD
	600/65 R 38	159 D 162 A8	DW 20 B	W 18 L	611	1745	790	5247	825	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			
			
		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baikrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026

SIZE	LI/SS	RIM		SW (mm)	OD (mm)	SLR (mm)	RC (mm)	SRI index	VERSION
		REC RIM	ALT RIM						
									
650/65 R 38	178 A8 175 B	DW 20 B	DW 21 B DW 23 B	645	1816	827	5488	875	SB
540/65 R 38	153 D 156 A8	W 16 L	W 18 L	530	1667	760	5059	800	STD
Ø42"									
650/65 R 42	165 D 168 A8	DW 20 B	DW 21 B DW 23 B	645	1913	878	5810	925	STD

SPL: SPECIAL, STD: STANDARD, SB: STEEL BELTED

TECHNOLOGIES		PERFORMANCES	
			  
		 	
		Permissible tolerances: 0.0. 2%–S.W. 2%–RC 2.5%–LI/SS load/speed index, S.W. tyre width 0.0. outer diameter of the tyre: SLR static radius, RC rolling circumference ; SRI index	

All images, texts and graphics contained in this document are the copyright of BKT. Permission is granted to print hard copies of this material. Any other form of reproduction, electronic or otherwise, as well as the application of any changes, partially or entirely, to images, texts, graphs and data is strictly prohibited without prior written permission by BKT. Baikrishna Industries Limited (BKT) reserves itself the right to alter any details contained in the publication without prior notice. BKT does not undertake any responsibility in relation to the exactness or correctness of information or illustrations contained in this document. BKT declines any direct or indirect liability for any material damage or personal injury which might arise directly or incidentally from the use of any information contained in this document. For any question in relation to specific operating issues always refer to the manufacturer of your vehicle or equipment.

US – 15/07/2026