


RIDEMAX IT 697 (M+S)

| | |
|--------------|--|
| TIRE SIZE | 710/70 R 38 IND |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ТРАКТОР-ТЯГАЧ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 177 D ; 182 A8 |



РАЗМЕРЫ IS STANDARD

| | | | |
|----------|------|---------|-----------------|
| SW (MM) | 716 | RIM REC | DW 23 B |
| OD (MM) | 1959 | RIM ALT | DW 25 B |
| SLR (MM) | 900 | ECE | E11-106R-006762 |
| RC (MM) | 5950 | SRI | 925 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 1.2 | 1.6 | 2.0 | 2.4 | 2.8 | 3.2 |
|------------|------|------|------|------|------|------|
| 65 | 3650 | 4455 | 4895 | 5770 | 6500 | 7300 |
| 50 | 3945 | 4810 | 5285 | 6230 | 7020 | 7885 |
| 40 | 4250 | 5185 | 5695 | 6715 | 7565 | 8500 |
| 30 | 4115 | 5345 | 5870 | 6925 | 7800 | 8760 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.