DATA SHEET

PRINTED ON
21-04-2026

AW 708

TIRE SIZE	**19.0/45 - 17**
UM	US STANDARD
CONSTRUCTION	
MACHINERY	BALER / IMPLEMENT MACHINERY / TRAILER / HARVESTER / IMPLEMENTS / TRAILER
VERSION	STANDARD
TIRE TYPE	TL
LI/SS FREE ROLLING	148 A8

DIMENSIONS US STANDARD

USA CODE	94010257	**RC (IN)**	99.8
SW (IN)	18.5	**RIM REC**	16.00
OD (IN)	34.1	**ECE**	E4-106R-002268
SLR (IN)	15.0	**PR**	18

LOAD CAPACITY (LBS/TIRE)

MPH / PSI	48
5 FR	9720
15 FR	8270
20 FR	7780
25 FR	6940

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..