


MULTIMAX MP 522

TIRE SIZE	400/80 R 24 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO / CARREGADORA COMPACTA / LEVANTADOR TELESCÓPICO
VERSÃO	STANDARD
TIRE TYPE	TL
LI/SS	162 A8/B



DIMENSÕES IS STANDARD

SW (MM)	404	RIM REC	DW 13
OD (MM)	1250	RIM ALT	DW 12 ; DW 13 L ; DW 14 L
SLR (MM)	565	ECE	E11-106R-002965
RC (MM)	3787	SRI	600

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.4	3.6	4.0	4.4	4.6	4.8	5.0	5.2	5.4
50	1855	2185	2565	2900	3230	3350	3520	3895	4220	4435	4540	4750	-	-
40	1855	2185	2565	2900	3230	3350	3520	3895	4220	4435	4540	4750	-	-
30	1985	2340	2750	3105	3460	3590	3770	4170	4515	4745	4860	5085	-	-
25	2060	2430	2850	3220	3590	3725	3910	4330	4690	4925	5040	5275	-	-
10 CYC.	2280	2785	3280	3850	4350	4600	4845	5280	5845	6090	6330	6655	6810	7125
STATIC	3500	4270	5030	5900	6670	7050	7430	8100	8960	9340	9710	10205	10445	10925

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.