


# BK-LOADER 53

<b>TIRE SIZE</b>	<b>405/70 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PALA CARGADORA
<b>VERSIÓN</b>	ARAMID BELTED
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	155A2/151A4



## DIMENSIONES IS STANDARD

<b>SW (MM)</b>	407	<b>RIM REC</b>	13
<b>OD (MM)</b>	1097	<b>RIM ALT</b>	14 ; 13 SDC; 12 ;12 SDC
<b>SLR (MM)</b>	511	<b>SRI</b>	525
<b>RC (MM)</b>	3339		

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.5	2.0	2.5	3.0	3.5	4.0	4.5	5.0	5.5
<b>20 TRANSPORT</b>	1210	1520	1805	2090	2375	2640	2905	3170	3450
<b>10 LOADING</b>	1375	1725	2050	2375	2700	3000	3300	3600	3875
<b>STATIC</b>	2200	2750	3275	3800	4325	4800	5300	5750	6200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.