


# AGRIMAX V-FLECTO



<b>TIRE SIZE</b>	<b>VF 710/55 R 38</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	TRATTORE A ELEVATA POTENZA / TRATTORE
<b>VERSIONE</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	175 D

## DIMENSIONI US STANDARD

<b>CODICE USA</b>	94067107	<b>RC (IN)</b>	206.4
<b>SW (IN)</b>	28.0	<b>RIM REC</b>	DW 25 B
<b>OD (IN)</b>	68.9	<b>RIM ALT</b>	DW 24 B
<b>SLR (IN)</b>	30.7	<b>ECE</b>	E11-106R-006844

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
45	6370	7340	8440	9410	10520	11490	12870	13830
<b>FROM 40 TO 25</b>	7000	8070	9280	10350	11560	12630	14150	15210
20	7140	8220	9470	10550	11790	12870	14430	15510
12	7290	8390	9660	10760	12030	13140	14720	15820
5	7700	8870	10210	11390	12720	13890	15560	16730
<b>*UPTO 5 CYC WITH FRONT LOADER</b>	9800	11290	13000	14480	16190	17680	19810	21300
5 HT	7140	8220	9470	10550	11790	12870	14430	15510

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.