


# AGRIMAX RT 765

	<b>260/70 R 20</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	ILAÇLAMA / TRAKTÖR / ÜZÜM HASAT MAKINESİ / BIÇERDÖVER / UYGULAMALI MAKİNE
<b>VERSION</b>	SPECIAL
<b>TIRE TYPE</b>	TL
	113 A8/B



## UNDEFINED US STANDARD

<b>USA CODE</b>	94044221	<b>RC (IN)</b>	103.9
<b>SW (IN)</b>	10.2	<b>RIM REC</b>	W 8
<b>OD (IN)</b>	34.3	<b>RIM ALT</b>	9; W 9
<b>SLR (IN)</b>	15.8	<b>ECE</b>	E4-106R-000640

## LOAD CAPACITY (LBS/TIRE)

MPH / PSI	9	12	15	17	20	23	29	35
30	1200	1380	1580	1770	1980	2180	2360	2540
25	1200	1380	1580	1770	1980	2180	2360	2540
20	1290	1480	1700	1910	2130	2350	2540	2720
5 LT	1610	1840	2120	2390	2670	2930	3170	3410
5 HT	1290	1480	1700	1910	2130	2350	2540	2720

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.