


MULTIMAX MP 522

TIRE SIZE	340/80 R 18 IND
UM	IS STANDARD
CONSTRUCTION	 RADIAL
MACHINERY	CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE / CHARGEUSE COMPACTE / CHARGEUSE TÉLESCOPIQUE
VERSION	STANDARD
TIRE TYPE	TL
LI/SS	143 A8/B



DIMENSIONS IS STANDARD

SW (MM)	343	RIM REC	11 ; 11 SDC ; W 11
OD (MM)	1006	RIM ALT	W 10 ; 12 ; 12 SDC
SLR (MM)	458	ECE	E4-106R-002654
RC (MM)	3023	SRI	475

LOAD CAPACITY (KG/TIRE)

KM/H / BAR	1.6	2.0	2.4	2.8	3.2	3.5	4.0	4.2	4.4
50	1310	1555	1775	2020	2265	2430	2725	-	-
40	1310	1555	1775	2020	2265	2430	2725	-	-
30	1405	1665	1900	2165	2425	2600	2920	-	-
25	1455	1725	1970	2240	2515	2695	3025	-	-
10 CYC.	1600	1965	2315	2660	3030	3295	3725	3930	4090
STATIC	2450	3010	3545	4080	4640	5050	5710	6020	6270

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.