

# AW 708

<b>TIRE SIZE</b>	<b>400/60 - 15.5</b>
<b>UM</b>	US STANDARD
<b>CONSTRUCTION</b>	⊠ BIAS
<b>MACHINERY</b>	BALPRESS / ARBETSFORDON / SLÄPVAGN / SKÖRDEMASKIN / ARBETSFORDON / SLÄPVAGN
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS FREE ROLLING</b>	145 A8



## DIMENSIONER US STANDARD

<b>USA CODE</b>	94010318	<b>RC (IN)</b>	100.9
<b>SW (IN)</b>	15.9	<b>RIM REC</b>	AG 13.00
<b>OD (IN)</b>	34.4	<b>ECE</b>	E4-106R-002712
<b>SLR (IN)</b>	15.0	<b>PR</b>	14

## LOAD CAPACITY (LBS/TIRE)

<b>MPH / PSI</b>	<b>52</b>
<b>5 FR</b>	8950
<b>15 FR</b>	7610
<b>20 FR</b>	7160
<b>25 FR</b>	6390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.