


# AGRIMAX RT 765

<b>TIRE SIZE</b>	<b>300/70 R 20</b>
<b>UM</b>	IS STANDARD
<b>CONSTRUCTION</b>	 RADIAL
<b>MACHINERY</b>	PULVERIZATOR / TRACTOR / MAȘINĂ DE RECOLTAT PODGORII / MAȘINĂ DE RECOLTARE / MAȘINI DE IMPLEMENTARE
<b>VERSION</b>	STANDARD
<b>TIRE TYPE</b>	TL
<b>LI/SS</b>	120 A8/B



## DIMENSIUNI IS STANDARD

<b>SW (MM)</b>	295	<b>RIM REC</b>	W 9
<b>OD (MM)</b>	952	<b>RIM ALT</b>	W 10
<b>SLR (MM)</b>	428	<b>ECE</b>	E4-106R-000643
<b>RC (MM)</b>	2854	<b>SRI</b>	450

## LOAD CAPACITY (KG/TIRE)

KM/H / BAR	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	660	760	870	980	1095	1205	1305	1400
40	660	760	870	980	1095	1205	1305	1400
30	705	810	930	1050	1170	1290	1395	1500
10 LT	885	1020	1170	1320	1470	1620	1750	1880
10 HT	705	810	930	1050	1170	1290	1395	1500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.