

# TR 117

|                     |                              |
|---------------------|------------------------------|
| <b>TIRE SIZE</b>    | <b>11.2 - 38</b>             |
| <b>UM</b>           | US STANDARD                  |
| <b>CONSTRUCTION</b> | ⊠ BIAS                       |
| <b>MACHINERY</b>    | PIVOT IRRIGATOR / IMPLEMENTS |
| <b>VERSION</b>      | STANDARD                     |
| <b>TIRE TYPE</b>    | TT                           |
| <b>LI/SS</b>        | 106 A8                       |



## DIMENSIONS US STANDARD

|                 |          |                |                |
|-----------------|----------|----------------|----------------|
| <b>USA CODE</b> | 94028801 | <b>RC (IN)</b> | 173.2          |
| <b>SW (IN)</b>  | 11.2     | <b>RIM REC</b> | W 10           |
| <b>OD (IN)</b>  | 56.9     | <b>RIM ALT</b> | W 9            |
| <b>SLR (IN)</b> | 26.6     | <b>ECE</b>     | E4-106R-002747 |

## LOAD CAPACITY (LBS/TIRE)

| MPH / PSI | 18   | 25   |
|-----------|------|------|
| 25        | 2090 | ---  |
| CREEP     | ---  | 4420 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.