

AGRIMAX RT 765

| | |
|---------------------|--|
| TIRE SIZE | 480/70 R 38 |
| UM | IS STANDARD |
| CONSTRUCTION |  RADIAL |
| MACHINERY | ОПРЫСКИВАТЕЛЬ / ТРАКТОР-ТЯГАЧ / КОМБАЙН ДЛЯ УБОРКИ ВИНОГРАДА / КОМБАЙН / СЕЛЬСКОХОЗЯЙСТВЕННОЕ ОБОРУДОВАНИЕ |
| VERSION | STANDARD |
| TIRE TYPE | TL |
| LI/SS | 145 D |



РАЗМЕРЫ IS STANDARD

| | | | |
|-----------------|------|----------------|-----------------|
| SW (MM) | 479 | RIM REC | W 15 L |
| OD (MM) | 1681 | RIM ALT | W 14 L; W 16 L |
| SLR (MM) | 764 | ECE | E11-106R-005832 |
| RC (MM) | 5055 | SRI | 800 |

LOAD CAPACITY (KG/TIRE)

| KM/H / BAR | 0.6 | 0.8 | 1.0 | 1.2 | 1.4 | 1.6 |
|------------|------|------|------|------|------|------|
| 65 | 1595 | 1860 | 2120 | 2380 | 2640 | 2900 |
| 50 | 1675 | 1950 | 2225 | 2500 | 2775 | 3045 |
| 40 | 1750 | 2040 | 2325 | 2610 | 2895 | 3180 |
| 30 | 1835 | 2135 | 2435 | 2735 | 3035 | 3335 |
| 10 LT | 2140 | 2490 | 2840 | 3190 | 3540 | 3890 |
| 10 HT | 1935 | 2135 | 2435 | 2735 | 3035 | 3335 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.