



US standard



GROWING TOGETHER

# SL 441



PRODUCT DATA SHEET



Bias



Performance



Durability



High Load Capacity



# SL 441

SL 441 is a tire developed for soil tillage and haulage operations with trailers and implement machinery. SL 441 has been engineered to offer great load capacity and a long tire life-cycle.

	US CODE	Tire size	RIM		S.W. (In.)	O.D. (In.)	SLR (In.)	RC (In.)	TREAD DEPTH (32nds)	TIRE WEIGHT (lbs)	Version	PR	Type	LI/SS	
			Rec.	Alt.										DW	FR
<b>14.5"</b>	94011087	200/60 - 14.5	AG 6.75	-	8.3	24.0	10.9	70.3	7	20	STD	10	TT	-	106 A8
	94025725	200/60 - 14.5	AG 6.75	-	8.3	24.0	10.9	70.3	7	24	STD	14	TL	-	113 A8
	94011094	200/60 - 14.5	AG 6.75	-	8.3	24.0	10.9	70.3	7	23	STD	14	TT	-	113 A8

STD: Standard



Tolerances: O.D. ± 2% - S.W. ± 2% - RC ± 2.5% - LI/SS = Load Index / Speed Symbol; S.W. = Section Width; O.D. = Overall Diameter; SLR = Static Loaded Radius; RC = Rolling Circumference; DW = Drive Wheel; FR = Free Rolling